

# Herkules 3400

## White PE-Foam Tape with Acrylic Adhesive

Created: 2007-03-20  
Updated: 2018-01-04

### GENERAL INFORMATION

---

Herkules 3400 is a white double sided tape with a cross-linked polyethylene carrier coated with an acrylic adhesive. It has a strong adhesive strength, holding power, weatherability, and good sealing properties.


- 1,00mm thick
- Acrylic adhesive
- Temperature resistant up to 90°C
- Good conformity for curved surfaces

Herkules 3400 can be die-cut for custom made parts and is available in all dimensions but standard widths are:

- 12mm x 50m
- 19mm x 50m
- 25mm x 50m
- 50mm x 50m

### CONSTRUCTION

---



### APPLICATIONS

---

Herkules 3400 bonds well on most surfaces and materials and has a strong adhesion, which makes it suitable for applications in various industries and applications requiring permanent and strong bonding. It is suitable for both indoor and outdoor applications, for example:

- Adhering car exterior parts such as decorative strips, tail wing, wheel arc, brake light
- Adhering car interior parts
- Emblems, nameplates and signs
- Other permanent bonding applications

### USER GUIDELINES

---

To obtain optimal adhesion the surfaces must be clean and dry. Most frequent cleaning solvent is isopropyl/water (50:50 mixture) alcohol. Use safety instructions before using cleaners. Sometimes depending on surface a primer can be used to obtain a higher bonding force. Ideal temperature for tape application is between 21°C and 38°C.

## PRODUCT DATA

---

### Physical Data:

Adhesive:	Acrylic
Carrier:	Cross-linked polyethylene foam (PE-foam) 64kg/m <sup>3</sup>
Thickness:	1,00mm
Liner:	Red siliconised paper
Colour:	White
Shelf life*:	2 years
Storage:	Good storage conditions are in room temperature.

\* From date of dispatch by ATC Tape Converting AB

### Performance Data:

Holding power: A/B side (PSTC-1)	24 hrs 1kg/25mm <sup>2</sup>
Holding power for temp resistance 60°C:	24 hrs 0,5kg/25mm <sup>2</sup>
Adhesion: A/B side (PSTC-)	19,52 – 24.40 N/25mm
Adhesion: 304 Stainless steel	>2 000 g/25mm
Initial tack: A/B side (PSTC-6#14 ball)	5,0 cm
Heat resistance:	Up to +90°C
Solvent resistance:	Good
UV-resistance:	Good
Age resistance:	Good

## CONTACT INFORMATION

---

### ATC Adhesive Tape Converting AB

Veddestavägen 17, Box 575  
175 26 Järfälla, SWEDEN

Telephone: +46 (0)8-564 708 80  
Fax: +46 (0)8-564 708 89

E-mail: [info@atc.se](mailto:info@atc.se)  
Web: [www.atc.se](http://www.atc.se)



**Intertek Intertek**