

Jupiter 3071

Smooth Marking Tape with Acrylic Adhesive

Created: 2011-09-14
Updated: 2018-01-04

GENERAL INFORMATION



Jupiter 3071 is a highly effective and durable aisle marking tape with high quality adhesive. This tape is slightly thinner and does not have as structured surface as Jupiter 3070.

- 0,83mm thick
- Acrylic adhesive
- Available in a wide range of colours
- Smoother surface

Jupiter 3071 can be die-cut for custom made parts and is available in all dimensions but standard widths are:

- 50mm x 30m
- 75mm x 30m
- 100mm x 30m

CONSTRUCTION



- White paper liner
- Acrylic adhesive
- PVC carrier with printed surface
- Top laminate of clear PVC

APPLICATIONS

Jupiter 3071 is a floor marking tape that can be used for a wide range of applications in industrial facilities. It can be used for general floor marking or can be die cut to specific shapes and figures for detailed and specialized marking.

- General aisle marking
- Floor marking in industrial facilities

USER GUIDELINES

To obtain optimal adhesion the surfaces must be clean and dry. Most frequent cleaning solvent is isopropyl/water (50:50 mixture) alcohol. Use safety instructions before using cleaners. Sometimes depending on surface a primer can be used to obtain a higher bonding force. Ideal temperature for tape application is between 21 °C and 38 °C.

PRODUCT DATA

Physical Data:

| | |
|--------------|--|
| Adhesive: | Acrylic |
| Carrier: | Top laminate: clear PVC Bottom carrier: PVC |
| Thickness: | Laminate: 0,50mm Carrier: 0,15mm Adhesive: 0,18mm Total: 0,83mm |
| Liner: | Red film |
| Colour: | Yellow, fluorescent yellow, green, red, white, blue, orange, black, black/yellow, red/white |
| Shelf life*: | 2 years |
| Storage: | Good storage conditions are in room temperature. Not recommended for direct exposure to sunlight or ultraviolet light. |

* From date of dispatch by ATC Tape Converting AB

Performance Data:

| | |
|--------------------------------|----------------|
| Tack loop: (PSTC-16) | 6,00 kg/25,4mm |
| Cohesion: (ASTM-7) | >24 hrs/25°C |
| Adhesion to steel: (PSTC-1) | 6,00 kg/25,4mm |

CONTACT INFORMATION

ATC Adhesive Tape Converting AB
Veddestavägen 17, Box 575
175 26 Järfälla, SWEDEN

Telephone: +46 (0)8-564 708 80
Fax: +46 (0)8-564 708 89

E-mail: info@atc.se
Web: www.atc.se

