

Jupiter 6060

Grey Anti Friction Tape with Acrylic Adhesive

Created: 2011-02-04
Updated: 2018-01-04

GENERAL INFORMATION

Jupiter 6060 is a single sided dimpled tape. Grey silicone coated cloth carrier with an aggressive acrylic adhesive and bonds well on many types of surfaces and materials.


- 0,8mm thick
- Acrylic adhesive
- Temperature resistant up to 80°C
- Good adhesion and bonding strength

Jupiter 6060 is available in all dimensions but standard widths are:

- 50mm x 25m
- 100mm x 25m



CONSTRUCTION



- Brown paper liner
- Solvent free acrylic adhesive
- Grey Silicone coated cloth carrier

APPLICATIONS

Jupiter 6060 specially designed as a anti friction tape for roller wrapping applications. The embossed surface prevents build-up of adhesive, ink and other deposit on web transport rollers. Jupiter 6060 is resistant against acids, liquids, oil and grease. Typical application areas are:

- Printing industries
- Building industry
- Textile industries
- General, web-based processing & converting industries

USER GUIDELINES

To obtain optimal adhesion the surfaces must be clean and dry. Most frequent cleaning solvent is isopropyl/water (50:50 mixture) alcohol. Use safety instructions before using cleaners. Sometimes depending on surface a primer can be used to obtain a higher bonding force. Ideal temperature for tape application is between 21°C and 38°C.

PRODUCT DATA

Physical Data:

Adhesive:	Solvent free acrylic
Carrier:	Grey silicone coated cloth carrier
Thickness:	0,8mm
Liner:	Brown siliconised paper
Colour:	Grey
Shelf life*:	12 months
Storage:	Good storage conditions are in room temperature. Not recommended for direct exposure to sunlight or ultraviolet light.

* From date of dispatch by ATC Tape Converting AB

Performance Data:

Peeling strength: Cohesion break (AFERA 4001)	35 N/25mm
Application temperature:	From -10°C
Heat resistance:	-40°C to +80°C
Condensation water resistance:	Very good
Ageing resistance:	Very good
Softener resistance:	Very good

CONTACT INFORMATION

ATC Adhesive Tape Converting AB

Veddestavägen 17, Box 575
175 26 Järfälla, SWEDEN

Telephone: +46 (0)8-564 708 80
Fax: +46 (0)8-564 708 89

E-mail: info@atc.se
Web: www.atc.se



Intertek Intertek